International Journal of Statistics and Applied Mathematics

ISSN: 2456-1452
Maths 2025, 10(5): 131-136

https://www.mathsjournal.com
Received: 04-03-2025
Accepted: 08-04-2025

Purnima
Assistant Professor, Guest Faculty, Applied Science Department, Ch Ranbir Singh State Institute of Engineering and Technology, Jhajjar, Haryana, India

Corresponding Author:
Purnima
Assistant Professor, Guest Faculty, Applied Science Department, Ch Ranbir Singh State Institute of Engineering and Technology, Jhajjar, Haryana, India

Busy period of the server and fraction number of inspections by repair man different three scenario of yarn industry

Purnima

DOI: https://www.doi.org/10.22271/maths.2025.v10.i5b.2046

Abstract
In this work, the yarn business is used as a case study to examine the dependability analysis of three unit systems using RPGT. When a single unit fails, the organization can work with less skill since units A, B, and D all consist of equivalent subcomponents. However, when two units are concentrated, the structure is considered to be in an unsuccessful state because it is not profitable to operate. Each of the three units has a distinct failure and repair rate. In order to quickly restore the broken units, one server is available 24/7. The problem is modeled using the units' constant disappointment/repair rates. It is necessary to study particular circumstances in order to investigate how overhaul rates and unhappiness affect organizational standards. The existing study resolve assist the companies in influential how many outmoded machinery they can buy on behalf of a precise amount of money. Proportional studies of the not compulsory method also give the organization an idea of which come near would give up the best outcome. Following tense tables, discussions and conclusions take place.

Keywords: RPGT, Busy Period of the server, failure rate, repair rate

1. Introduction

The needs of modern society and the development of science and technology collide. Today's competitive environment and people's increasing reliance on technology have forced industries to focus on peak system performance while keeping costs low. It is generally accepted that by focusing on the system's performance, significant improvement manifests itself in the form of lower costs, higher build quality, higher reliability, and better manufacturing. Our lives would be motionless or stopped without the modern conceptual systems that have been developed over the years. System reliability of industry or a merchandise is a central phase of superiority for its consistency act on its projected life phase. In huge complex systems resembling electric power production and giving out plants, a statement set-up system and a trustworthy service are important requirements. In such circumstances, a quick malfunction of a single element, unit may effect in a health threat, or failure of service. akin impulsive disappointment may happen in meting out productions which may in addition get destructive to the health of staff and the reputation of the companionship in the advertise, even though such collapse may become reason for the hassle on a smaller scale. consequently, paucities in the mean and built-up of such complex structure must be spotted by trying at an early increase stage and later corrected by a planned safeguarding line up.

Because of its rich soil and water supply brought about by geography and weather, the Abohor and Fazilka Districts in Punjab's Malwa region are well known across the world for producing cotton. Because of its abundance, the majority of the high-quality cotton produced in the region is exported to other parts of India and beyond, but a sizable portion is still leftover and utilized infrequently as a raw material for the yarn industry. Cotton mills treat row cotton in order to separate the cotton seeds from the raw cotton. After that, cotton bales are transported to various locations for marking. Because it is lucrative for a select few cotton farmers, self-employment, and work satisfaction for the local populace, the Malwa region is home to several yarn industries.

This is due to the fact that moving cotton bales to other places is more costly, time-consuming, and labor-intensive. The dependability analysis of three unit systems using machine learning is covered in this work (a case study of the textile industry). When a single unit fails, the organization can work with fewer resources since units A, B, and D all have comparable subcomponents. A number of assumptions, probabilities, and an aggregated transition representation of the system must be taken into account in order to find elements C0. Expressions for system parameters are derived. Ritikesh and Goel (2015) [10] this paper discusses about the behavior analysis of a system which has a single unit which go to degradation following having complete failure by the procedure of RPGT. At the initial stage the unit is doing work at complete capacity and this can have failure of two types, first one is the direct failure mode and second is by the partially failure.

Discussed the sensitivity analysis of 3:4:: smart system plant is shaped with a lonely server which contains of 4 non-indistinguishable units within which elementary unit will add diminish state thanks to partial failure using RPGT technique. Kumar *et al.*. (2019) [8] paper analyzed a sensitivity evaluation of a cold reserve device with precedence for defensive upkeep consist same devices with server disappointment the usage of RPGT. In this wok there are devices certainly considered individual among that is on-line at the same time as different is saved in cold standby mode? Single restore facility is to be had in 24*7. Tables & figures are installation to have a take a, observe and draw the conclusion. Rajbala *et al.*. (2019) [7] studied the structure modeling & psychoanalysis: A case revise EAEP manufacturing plant.

Rykov *et al.*. (2020) [6] studied on the reliability function of a k-out-of-n system through specific restore time distribution. Agrawal *et al.*. (2021) [5] discussed the profit analysis of a Water Treatment Reverse Osmosis Plant using the RPGT under specific conditions for scheme parameters. Kumari *et al.*. (2021) [4] studied on the explanation of constrained problems by particle swarm optimization. Garg and Garg (2022) [3] studied the presentation analysis of the briquette machine in view of a neglected fault with PM used the Artificial Bee Colony algorithm to optimize the assessment of system profit.

Rohit and Poonia (2023) [2] study focuses on the mathematical modeling and sensitivity analysis of a steel mill made up of four subsystems using RPGT; all subsystem's exponential disappointment and specific repair rates are explored.

Kumar *et et al.*. (2024) [1] examined the RAM properties of various process industry systems. It gives a summary of how RAM practices have evolved historically and how they stand today within the intricate web of industries.

2. Assumptions and Notations

- There are consistent and distinct distributions of let-down and repair times.
- The structure is as good as new after the repair, which is flawless.
- Switching is perfect.

λ_i $(1 \leq i \leq 6)$: Failure Rates

w_i $(1 \leq i \leq 6)$: Repair Rates

3. Transition Diagram Description

Considering the various possibilities and succeeding the assumptions of the structure is drawn as under in Figure 1.



Fig 1: Transition Diagram

$S_0 = ABD$, $S_1 = \bar{A}BD$, $S_2 = aBD$, $S_3 = A\bar{B}D$, $S_4 = AbD$, $S_5 = A\overline{BD}$,

$S_6 = AB\bar{D}$, $S_7 = \bar{A}B\bar{D}$, $S_8 = ABd$, $S_9 = \overline{AB}D$

4. Transition Probability

Now path probability of the system from the base position of system are given as

$V_{0,0} = 1$ (Verified)

$V_{0,1} = (\lambda_1 / \lambda_5 + \lambda_2 + \lambda_3 + w_1)/(\lambda_1 + \lambda_5 + \lambda_3)(\lambda_5 + \lambda_3 + w_1)$

$V_{0,2} = \lambda_1 \lambda_2 / (\lambda_1 + \lambda_5 + \lambda_3)(\lambda_5 + \lambda_3 + w_1)$

$V_{0,3} =$ …….Continuous

5. Methodology and Discussions

Busy Period of the Server: States where attendant is busy used for exploit a number of job are ‘i’ = 1 to 9, attractive ‘ξ’ = ‘0’,

$$B_0=\left[\sum_{j,sr}\left\{\frac{\{pr(\xi^{sr}\to j)\},nj}{\Pi_{m_{1\neq\xi}}\{1-V_{\overline{m_1m_1}}\}}\right\}\right]\div\left[\sum_{i,s_r}\left\{\frac{\{pr(\xi^{sr}\to i)\}\mu_i^1}{\Pi_{m_{2\neq\xi}}\{1-V_{\overline{m_2m_2}}\}}\right\}\right]$$

$$B_0=\left[\sum_j V_{\xi,j}\,,n_j\right]\div\left[\sum_i V_{\xi,i}\,,\mu_i^1\right]$$

$B_0=[\{(\lambda_1/\lambda_5+\lambda_2+\lambda_3+w_1)/(\lambda_1+\lambda_5+\lambda_3)(\lambda_5+\lambda_3+w_1)\mu_1\}$
$+V_{0,5}\mu_5+\{\lambda_5(\lambda_3+\lambda_6+\lambda_1+w_5)^2/(\lambda_1+\lambda_5+\lambda_3)(\lambda_6+\lambda_1+w_5)(\lambda_6+\lambda_3+w_5)$
$(\lambda_3+\lambda_1+w_5)+\lambda_3\lambda_5(\lambda_3+\lambda_6+\lambda_1+w_5)/(\lambda_5+\lambda_3+w_1)(\lambda_1+\lambda_5+\lambda_3)(w_3+\lambda_5+\lambda_4)$
$(\lambda_6\lambda_1+\lambda_6w_5+w_3\lambda_3+w_5\lambda_1+w_5^2)+\lambda_1\lambda_5(\lambda_3+\lambda_6+\lambda_1+w_5)^2/(\lambda_1+\lambda_5+\lambda_3)(\lambda_5+\lambda_3+w_1)$
$(\lambda_6\lambda_3+\lambda_6w_5+w_5\lambda_3+w_5\lambda_1+w_5^2)+\lambda_1\lambda_3\lambda_5(w_3+\lambda_1+\lambda_5+\lambda_4)(\lambda_3+\lambda_6+\lambda_1+w_5)^2/(\lambda_1+\lambda_5+\lambda_3)$
$(\lambda_5+\lambda_3+w_1)(w_3+\lambda_5+\lambda_4)(w_3+\lambda_1+\lambda_5)(\lambda_3w_5+\lambda_6\lambda_1+\lambda_6w_5+w_5\lambda_3+w_5\lambda_1+w_5^2+w_3\lambda_3)\mu_6\}$
$+\{\lambda_5\lambda_1(\lambda_3+\lambda_6+\lambda_1+w_5)^2/(\lambda_1+\lambda_5+\lambda_3)(\lambda_6+\lambda_1+w_5)(\lambda_3+\lambda_6+w_5)$
$+\lambda_1\lambda_5(\lambda_6+\lambda_1+w_3)(\lambda_3+\lambda_1+w_5)/(\lambda_1+\lambda_5+\lambda_3)(\lambda_5+\lambda_3+w_1)(\lambda_6\lambda_3+\lambda_6w_5+w_5\lambda_3+w_5\lambda_1+w_5^2)$
$+\lambda_3\lambda_5\lambda_1(w_3+\lambda_1+\lambda_5+\lambda_4)/(w_3+\lambda_6+\lambda_1+\lambda_5)/(\lambda_1+\lambda_5+\lambda_3)(w_3+\lambda_1+\lambda_5)(w_3+\lambda_5+\lambda_4)$
$(\lambda_6\lambda_1+\lambda_6w_5+w_5\lambda_3+w_5\lambda_1+w_5^2)+\lambda_1^2\lambda_3\lambda_5(w_3+\lambda_6+\lambda_1+\lambda_5)/(\lambda_1+\lambda_5+\lambda_3)(\lambda_5+\lambda_2+\lambda_3+w_1)$
$(\lambda_5+\lambda_3+w_1)(w_3+\lambda_5)(\lambda_6\lambda_1+\lambda_6w_5+w_5\lambda_3+w_5\lambda_1+w_5\lambda_1+w_5^2)\mu_7\}+\{\lambda_5\lambda_6(\lambda_3+\lambda_6+\lambda_1+w_5)^2$
$/(\lambda_1+\lambda_5+\lambda_3)(w_3+\lambda_5+\lambda_4)(\lambda_6\lambda_1+\lambda_6w_5+w_5\lambda_1+\lambda_3w_5+w_5^2)+\lambda_1\lambda_5\lambda_6(\lambda_3+\lambda_6+\lambda_1+w_5)/$
$(\lambda_1+\lambda_5+\lambda_3)(\lambda_5+\lambda_3+w_1)(\lambda_6\lambda_3+w_5\lambda_3+w_5\lambda_1+\lambda_6w_5+w_5^2)+\lambda_1\lambda_3\lambda_5\lambda_6(w_3+\lambda_6+\lambda_1+\lambda_5)$
$/(\lambda_5+\lambda_3+w_1)(\lambda_3w_5+\lambda_6\lambda_1+\lambda_6w_5+w_5\lambda_1+w_5\lambda_1+w_5^2)\mu_8\}\mu_9)\}]/k=(1-\mu_0/k)$

Expected fraction Number of Inspections by repair man: The re-forming states where the restoration man visit afresh are states 1, 3 and 6 to do this job the digit of visit thru the repair man stands known by

$$V_0=\left[\sum_{j,sr}\left\{\frac{\{pr(\xi^{sr}\to j)\}}{\Pi_{k_{1\neq\xi}}\{1-V_{\overline{k_1k_1}}\}}\right\}\right]\div\left[\sum_{i,s_r}\left\{\frac{\{pr(\xi^{sr}\to i)\}\mu_i^1}{\Pi_{k_{2\neq\xi}}\{1-V_{\overline{k_2k_2}}\}}\right\}\right]=\left[\sum_j V_{\xi,j}\right]\div\left[\sum_i V_{\xi,i}\,,\mu_i^1\right]$$

$V_0=\{(\lambda_1/\lambda_5+\lambda_2+\lambda_3+w_1)/(\lambda_5+w_3)\}\}+\{\lambda_5(\lambda_6+w_5)^2/(\lambda(\lambda_6+\lambda_1+w_5)(\lambda_6+\lambda_3+w_5)(\lambda_3+\lambda_1+w_5)$
$+\lambda_3\lambda_5(\lambda_5+\lambda_2+\lambda_3+w_1)(\lambda_3+\lambda_6+\lambda_1+w_5)/(\lambda_5+\lambda_3+w_1)(\lambda_1+\lambda_5+\lambda_3)(w_3+\lambda_5+\lambda_4)$
$(\lambda_6\lambda_1+\lambda_6w_5+w_3\lambda_3+w_5\lambda_1+w_5^2)+\lambda_1\lambda_5(\lambda_3+\lambda_6+\lambda_1+w_5)^2/(\lambda_1+\lambda_5+\lambda_3)(\lambda_5+\lambda_3+w_1)$
$(\lambda_6\lambda_3+\lambda_6w_5+w_5\lambda_3+w_5\lambda_1+w_5^2)+\lambda_1\lambda_3\lambda_5(w_3+\lambda_1+\lambda_5+\lambda_4)(\lambda_3+\lambda_6+\lambda_1+w_5)^2/(\lambda_1+\lambda_5+\lambda_3)$
$(\lambda_5+\lambda_3+w_1)(w_3+\lambda_5+\lambda_4)(w_3+\lambda_1+\lambda_5)(\lambda_3w_5+\lambda_6\lambda_1+\lambda_6w_5+w_5\lambda_3+w_5\lambda_1+w_5^2+w_3\lambda_3)\}/k$

5.1 Particular different Scenario’s

Scenario 1: $w_i\ (1\le i\le 6)=w;\ \lambda_i\ (1\le i\le 6)=\boldsymbol{\lambda}$

Busy period of server (BPOS) (B_0)

Table 1: BPOS

$\boldsymbol{\lambda}$ w	0.50	0.60	0.70
0.10	7.88	7.78	7.68
0.20	7.90	7.80	7.70
0.30	7.92	7.82	7.72



Fig 2: BPOS

Expected Fractional Number of Inspections by Repairman (EFNIR) (V_0)

Table 2: EFNOR

$\boldsymbol{\lambda}$ **w**	**0.50**	**0.60**	**0.70**
0.10	.56	.58	.60
0.20	.60	.62	.64
0.30	.64	.66	.68



Fig 3: EFNIR

Scenario 2: Sensitivity analysis w. r. t. variation in repair rates**.** Attractive$\lambda_i = 0.15$ $(1 \leq i \leq 6)$ and unpredictablew_i $(1 \leq i \leq 6)$ one-to-one at 0.60, 0.65, 0.70, 0.75, 0.80, 0.85

Table 3: BPOS

w_i	w_1	w_2	w_3	w_4	w_5	w_6
0.60	0.646	0.652	0.658	0.664	0.670	0.676
0.65	0.640	0.646	0.652	0.658	0.664	0.670
0.70	0.634	0.640	0.646	0.652	0.658	0.664
0.75	0.628	0.634	0.640	0.646	0.652	0.658
0.80	0.622	0.628	0.634	0.640	0.646	0.652
0.85	0.616	0.622	0.628	0.634	0.640	0.646



Fig 4: BPOS

Table 4: EFNIR

w_i	w_1	w_2	w_3	w_4	w_5	w_6
0.60	0.114	0.112	0.110	0.108	0.106	0.104
0.65	0.116	0.114	0.112	0.110	0.108	0.106
0.70	0.118	0.116	0.114	0.112	0.110	0.108
0.75	0.120	0.118	0.116	0.114	0.112	0.110
0.80	0.122	0.120	0.118	0.116	0.114	0.112
0.85	0.124	0.122	0.120	0.118	0.116	0.114



Fig 5: EFNIR

Scenario 3

Currently one reflects sensitivity analysis scenario 2 for vagaries in disappointment rates: enchanting repair rates $w_i = 0.85$ $(1 \leq i \leq 6)$ and erratic λ_I $(1 \leq i \leq 6)$ one by one respectively at 0.10, 0.15, 0.20, 0.25, 0.30 and 0.35.

Table 5: BPOS

λ_i	λ_1	λ_2	λ_3	λ_4	λ_5	λ_6
0.10	0.58	0.47	0.36	0.25	0.14	0.03
0.15	0.69	0.58	0.47	0.36	0.25	0.14
0.20	0.80	0.69	0.58	0.47	0.36	0.25
0.25	0.91	0.80	0.69	0.58	0.47	0.36
0.30	1.02	0.91	0.80	0.69	0.58	0.47
0.35	1.13	1.02	0.91	0.80	0.69	0.58



Fig 6: BPOS

Table 6: EFNIR

λ_i	λ_1	λ_2	λ_3	λ_4	λ_5	λ_6
0.10	0.58	0.56	0.54	0.52	0.50	0.48
0.15	0.60	0.58	0.56	0.54	0.52	0.50
0.20	0.62	0.60	0.58	0.56	0.54	0.52
0.25	0.64	0.62	0.60	0.58	0.56	0.54
0.30	0.66	0.64	0.62	0.60	0.58	0.56
0.35	0.68	0.66	0.64	0.62	0.60	0.58



Fig 7: EFNIR

5. Conclusions

According to this concept, we take care of the system for a long time and a repair facility maintained by repairmen should be provided in working condition. The concept of listening means a lesson in understanding the factors or reasons that cause system failure. Nowadays there is a competitive era whereby each industry competes with each other to increase production and increase customer demand. Brand reliability and customer satisfaction depend on the system; ability to deliver products and services on time. So for this the system must be accessible, but functional process and working system reduce their capacity, performance and reliability, when the subunits/units of systems fail and sometimes they do not benefit from timely maintenance or temporary maintenance and in some cases Repair is only possible when the unit is completely damaged by the unit or its subunits continue to fail. Table 1 and Figure 2 above demonstration that as the rate of failure increases and the rate of repair decreases, the duration of the busy period expands. A logical set of assumptions or assertions put forth in an attempt to explain a phenomenon is what is known as a theory. A viewpoint, presumption, frame of reference, vision, or perspective is called an idea. Table 2 shows that the EFNIR grows with increasing failure rates and falls with increasing repair rates. The monetary device and the commercial member of the family device aren't necessarily synonymous; in certain aspects, they overlap, and in other others, they have different applications. The graph 3 indicates that as the failure rates increase, expected number of server visits rises, and as repair rates increase, EFNIR reduces. It was determined in table 3 and figure 4 that the repairmen should be effective in fixing unit first in order to diminish the busy time aimed at the server. So for this the system must be accessible, but functional process and working system reduce their capacity, performance and reliability, when the subunits/units of systems fail and sometimes they do not benefit from timely maintenance or temporary maintenance and in some cases Repair is only possible when the unit is completely damaged by the unit or its subunits continue to fail. According to Figure 4 and Table 5, number of calls from the server would be reserved to a minimum while moving in segments as of top to bottom. From Figure 5 and Table 6, we appreciate that the optimal value of the busy period is 1.13, which recommends that the disappointment rate of unit is highest. After table 6, it is determined that estimation of to rise at a quicker rate on expanding the disappointment rate of sub-unit rise, the same pattern is appreciated in Figure 7.

6. References

1. Kumar P, Kumar D, Chalisgaonkar R, Sharma VK, Rai KS. A critical review of Ram methodology: analysis and performance evaluation in industrial complexities. Reliab Theory Appl. 2024;83-89.
2. Rohit, Poonia MS. Sensitivity analysis of a steel industrial plant in Hisar district using RPGT. Eur Chem Bull. 2023;17816-17823.
3. Garg D, Garg R. Performance analysis of the briquette machine considering a neglected fault with preventive maintenance. Int J Syst Assur Eng Manag, 2022, p. 1-8.
4. Kumari S, Khurana P, Singla S, Kumar A. Solution of constrained problems using particle swarm optimization. Int J Syst Assur Eng Manag, 2021, p. 1-8.
5. Agrawal A, Garg D, Kumar A, Kumar R. Performance analysis of the water treatment reverse osmosis plant. Reliab Theory Appl, 2021, p. 16-25.
6. Rykov V, Kozyrev D, Filimonov A, Ivanova N. On reliability function of a k-out-of-n system with general repair time distribution. Probabil Eng Inform Sci, 2020, p. 885-902.
7. Rajbala A, Kumar A, Garg D. Systems modeling and analysis: a case study of EAEP manufacturing plant. Int J Adv Sci Technol, 2019, p. 250-259.
8. Kumar A, Garg D, Goel P. Sensitivity analysis of a cold standby system with priority for preventive maintenance. J Adv Scholarly Res in Allied Educ, 2019, p. 253-258.
9. Kumar A, Garg D, Goel P, Ozer O. Sensitivity analysis of 3:4:: good system. Int J Adv Res Sci Eng, 2018, p. 851-862.
10. Ritikesh, Goel P. Availability modeling of single unit system subject to degradation post repair after complete failure. In: Proc Int Conf Innov Res Eng Sci Manag, 2015, p. 57-65.